



## SL-FX2835CC12-120

กระแสดังที่ ได้มากถึง 20 เมตร

### Application

SL-FX2835CC12-120 Designed for linear light applications.

- Architectural lighting
- Interior lighting
- Customized lighting design

### Specification

Coded	: SL-FX2835CC12-120
LED Type	: SMD2835
Life time	: 30000 Hrs.
CRI	: >Ra 80 Normal
CCT	: 3000K, 4200K, 6500K
System Efficacy	: 140LM/M
LEDs/M	: 120LED
FPCB/mm	: 8mm.
Input Voltage	: DC 24VDC
System Power Consumption	: 12W/m
IP Rating	: 20
Operating Temperature	: -20°~50°C
Package	: 5M./Roll

- เหมาะสำหรับให้แสงสว่างและตกแต่งบริเวณพื้นที่จำกัดเช่นห้องครัว ชั้นวางสินค้า ผังห้องตู้เสื้อผ้า และอื่นๆ

### Accessories




Perwer supply 24VDC




Perwer supply 12VDC


### Neon Silicone Tube



SL-N0816B



SL-N1023B



SL-N1220B

### Aluminum Profile



SL-ALC1806



SL-ALD003C




SL-ALA1707



SL-ALA1616



SL-AL2507



SL-AL1110



### Self lighting Solution

